



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/710,596	07/23/2004	Mou-Shiung Lin	MEGP0027USA4	4595

27765 7590 12/23/2008
NORTH AMERICA INTELLECTUAL PROPERTY CORPORATION
P.O. BOX 506
MERRIFIELD, VA 22116

EXAMINER

MATTHEWS, COLLEEN ANN

ART UNIT	PAPER NUMBER
----------	--------------

2811

NOTIFICATION DATE	DELIVERY MODE
-------------------	---------------

12/23/2008

ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

winstonhsu.uspto@gmail.com
Patent.admin.uspto.Rcv@naipo.com
mis.ap.uspto@naipo.com.tw

Office Action Summary	Application No. 10/710,596	Applicant(s) LIN, MOU-SHIUNG	
	Examiner Colleen A. Matthews	Art Unit 2811	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 09/25/2008.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 43-74, 83, 84 and 89-102 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 43-74, 83, 84 and 89-102 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 09/25/2008 has been entered.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 43, 48-53, 89 and 94-99 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery).

Re claim 43: Lin discloses a chip structure comprising:

a silicon substrate (10, col 4 line 49);

a resistor in said silicon substrate (not shown but "transistors and other devices" is described in col 4 lines 49-51),

Art Unit: 2811

a MOS device (not shown but described as “transistors and other devices” in col 4 lines 49-51) comprising a portion in said silicon substrate;

a metallization structure (14) over said silicon substrate, wherein said metallization structure comprises a first metal layer (interconnect portion 13 of first layer of 14) and a second metal layer (interconnect portion 13 of second layer of 14) over said first metal layer;

a first dielectric (white portion of layer 14) layer between said first and second metal layers;

a passivation layer (18, col 5 lines 4-5) over the metallization structure and over said dielectric layer, wherein a first opening in said passivation layer is over a first contact point (16) of said metallization structure and said first contact point is at a bottom of said first opening, and a second opening (16) in said passivation layer is over a second contact point of said metallization structure and said second contact point is at a bottom of said second opening, where said first and second contact points are separated from each other by an insulating material (the passivation layer 18), wherein said passivation layer comprises an insulating nitride layer (col 5 lines 4-5); and

a circuit trace (26/22/36/28/38) over the passivation layer and over said first and second contact points (16), wherein said first contact point is connected to said second contact point through said circuit trace (38/28/38 connect first and second points 16), and wherein said circuit trace is connected to said resistor (col 4 lines 66-67, col 5 line 1-2 describe point of contact 16 as connected to the transistors and other devices on the surface of substrate 10, which would include the resistor. col 5 lines describe

Art Unit: 2811

contact point 16 also in electrical contact with 22/36/38, which is the circuit trace. Thus the resistor on surface of substrate is connected to the circuit trace through contact 16) through said first opening (16).

Lin fails to disclose the resistor in said silicon substrate comprises silicon with a dopant. Woolery teaches a chip structure (Figures 4A-4J) with a silicon substrate (400) and a resistor ("Resistor") in said silicon substrate, where said resistor comprises silicon with a dopant (arsenic, col 9 lines 53-56). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to have a resistor in the silicon substrate where said resistor comprises silicon with a dopant as in Woolrey in order to be able to predetermine and set the device resistivity.

Re claim 89: Lin discloses a chip structure comprising:

a silicon substrate (10, col 4 line 49);

a resistor in said silicon substrate (not shown but "transistors and other devices" is described in col 4 lines 49-51),

a MOS device (not shown but described as "transistors and other devices" in col 4 lines 49-51) comprising a portion in said silicon substrate;

a metallization structure (14) over said silicon substrate, wherein said metallization structure comprises a first metal layer (interconnect portion 13 of first layer of 14) and a second metal layer (interconnect portion 13 of second layer of 14) over said first metal layer;

a dielectric (white portion of layer 14) layer between said first and second metal layers;

Art Unit: 2811

a passivation layer (18, col 5 lines 4-5) over the metallization structure and over said dielectric layer; wherein a first opening in said passivation layer is over a first contact point (16) of said metallization structure and said first contact point is at a bottom of said first opening, and wherein a second opening (16) in said passivation layer is over a second contact point of said metallization structure and said second contact point is at a bottom of said second opening, where said first and second contact points are separated from each other by an insulating material (the passivation layer 18) and wherein said passivation layer comprises an insulating nitride layer (col 5 lines 4-5)

a circuit trace (26/22/36/28/38) over the passivation layer and over said first and second contact points (16), wherein said first contact point is connected to said second contact point through said circuit trace (38/28/38 connect first and second points 16),, wherein said circuit trace is connected to said resistor (col 4 lines 66-67, col 5 line 1-2 describe point of contact 16 as connected to the transistors and other devices on the surface of substrate 10, which would include the resistor. col 5 lines describe contact point 16 also in electrical contact with 22/36/38, which is the circuit trace. Thus the resistor on surface of substrate is connected to the circuit trace through contact 16) through said first opening (16)., and wherein said circuit trace comprises a third metal layer (copper, tungsten, nickel col 6 lines 55-57) and a copper layer (electroplating copper, col 6 lines 57) over said third metal layer.

Lin fails to disclose the resistor in said silicon substrate comprises silicon with a dopant. Woolery teaches a chip structure (Figures 4A-4J) with a silicon substrate (400)

Art Unit: 2811

and a resistor ("Resistor") in said silicon substrate, where said resistor comprises silicon with a dopant (arsenic, col 9 lines 53-56). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to have a resistor in the silicon substrate where said resistor comprises silicon with a dopant as in Woolrey in order to be able to predetermine and set the device resistivity.

Re claims 48-53 and 94-99: Lin discloses a polymer layer (20) on the passivation layer (18) and the circuit trace (26/22/21/36/28) and wherein said circuit trace is further on the polymer layer and the polymer layer comprises polyimide (PI) or benzocyclobutene (BCB), (col 5, lines 19 and 23-27).

Claims 54-59 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) and U.S. Pat. No. 6,235,101 to Erdejac et al. (Erdejac).

Re claims 54-58: Lin discloses the circuit structure as claimed in 43. Lin fails to explicitly disclose the structure comprising an inductor over said passivation layer where said inductor comprises a copper layer. Erdejac teaches an inductor (top metal inductor Fig 20c) over said passivation layer where said inductor comprises: a copper layer (col 6 lines 65-68); a gold layer (col 7 line 25-26); or a titanium-tungsten alloy layer and a copper layer over said titanium-tungsten alloy layer (col 6 lines 57-60). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to have the inductor as in Erdejac in order to create a circuit structure for specific applications such as RF.

Art Unit: 2811

Re claim 59: Lin discloses the circuit structure as claimed in 43. Lin fails to explicitly disclose the structure comprising a capacitor over said silicon substrate. Erdejac teaches a capacitor (Fig 20b, poly poly capacitor) over said silicon substrate, where said capacitor comprises a first electrode (poly 0) over the substrate, wherein a third opening in the passivation layer is over the first electrode and the first electrode has a top surface at the bottom of said third opening, a second electrode over said top surface and a second dielectric layer between the top surface and the second electrode (poly 1). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to include the capacitor as in Erdejac in order to create a circuit structure for specific applications such as RF.

Claims 64, 60-63, 69-74, 83-84 and 100-102 are rejected under 35 U.S.C.

103(a) as being unpatentable over U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) and U.S. Pat. No. 6,486,530 to Sasagawa et al. (Sasagawa) or U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) and U.S. Pat. No. 6,235,101 to Erdejac et al. (Erdejac) and U.S. Pat. No. 6,486,530 to Sasagawa et al. (Sasagawa).

Re claim 64: Lin discloses a chip structure comprising:

a silicon substrate (10, col 4 line 49);

a resistor in said silicon substrate (not shown but “transistors and other devices” is described in col 4 lines 49-51),

Art Unit: 2811

a MOS device (not shown but described as “transistors and other devices” in col 4 lines 49-51) comprising a portion in said silicon substrate;

a metallization structure (14) over said silicon substrate, wherein said metallization structure comprises a first metal layer (interconnect portion 13 of first layer of 14) and a second metal layer (interconnect portion 13 of second layer of 14) over said first metal layer;

a dielectric (white portion of layer 14) layer between said first and second metal layers;

a passivation layer (18, col 5 lines 4-5) over the metallization structure and over said dielectric layer, herein a first opening in said passivation layer is over a first contact point (16) of said metallization structure and said first contact point is at a bottom of said first opening, and wherein a second opening (16) in said passivation layer is over a second contact point of said metallization structure and said second contact point is at a bottom of said second opening, where said first and second contact points are separated from each other by an insulating material (the passivation layer 18), wherein said passivation layer comprises an insulating nitride layer (col 5 lines 4-5); and

a circuit trace (26/22/36/28/38) over the passivation layer and over said first and second contact points (16), wherein said first contact point is connected to said second contact point through said circuit trace (38/28/38 connect first and second points 16), wherein said circuit trace is connected to said resistor (col 4 lines 66-67, col 5 line 1-2 describe point of contact 16 as connected to the transistors and other devices on the surface of substrate 10, which would include the resistor. col 5 lines describe contact

Art Unit: 2811

point 16 also in electrical contact with 22/36/38, which is the circuit trace. Thus the resistor on surface of substrate is connected to the circuit trace through contact 16) through said first opening (16).

Lin fails to disclose the resistor in said silicon substrate comprises silicon with a dopant. Woolery teaches a chip structure (Figures 4A-4J) with a silicon substrate (400) and a resistor ("Resistor") in said silicon substrate, where said resistor comprises silicon with a dopant (arsenic, col 9 lines 53-56). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to have a resistor in the silicon substrate where said resistor comprises silicon with a dopant as in Woolery in order to be able to predetermine and set the device resistivity.

Lin also fails to disclose where said circuit trace comprises a titanium-containing layer and a gold layer over said titanium-containing layer. Sasagawa teaches a circuit trace (109-111) comprises a titanium-containing layer (109, col 4 line 14) and a gold layer (111, col 4 line 21) over said titanium-containing layer. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to include the different circuit trace and metallization layers of Sasagawa in order to optimize the device performance under thermal stress.

Re claims 60-63, 83-84 and 100-102: Lin as modified discloses the device of 43, 65 and 89 as above where the circuit trace comprises a nickel layer over a copper layer. Lin fails to disclose the circuit trace comprising aluminum or a gold layer over the copper layer, a titanium layer under the copper layer, a titanium-containing layer comprising tungsten, a chromium layer under the copper layer, a gold layer, a titanium-

Art Unit: 2811

containing layer under gold layer and a titanium-containing layer comprising tungsten. a Sasagawa teaches a circuit trace/capacitor second electrode (109-111) comprises aluminum, or nickel layer over a copper layer and the circuit trace comprising a gold layer over the copper layer, a titanium layer under the copper layer, a chromium layer under the copper layer, a gold layer, a titanium-containing layer under gold layer and a titanium-containing layer (col 4 lines 13-22). Erdejac teaches a titanium-containing layer comprising a titanium-tungsten alloy (col 6 lines 57-60).. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to include the different circuit trace and metallization layers of Sasagawa and Erdejac in order to optimize the device performance under thermal stress.

Re claims 69-74: Lin discloses a polymer layer (20) between the passivation/silicon-nitride layer (18) and the circuit trace (26/22/21/36/28) and on the circuit trace where the polymer layer comprises polyimide (PI) or benzocyclobutene (BCB), (col 5, lines 19 and 23-27).

Claims 44-46, 65-67, 90-92 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) as applied to claims 44 and 89 above and U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) and U.S. Pat. No. 6,486,530 to Sasagawa et al. (Sasagawa) as applied to claim 64 above and in further view of U.S. Pub. No. 2003/0155570 to Leidy.

Art Unit: 2811

Re claims 44-46, 65-67, 90-92, Lin as modified discloses the device of 43, 65, and 89 as above. The modification of Woolery also discloses the resistor comprising silicon with a dopant of arsenic (col 9 lines 51 line 6). Lin as modified fails to disclose the resistor comprising silicon with a dopant of boron, phosphorous. Leidy teaches a resistor comprising silicon and a dopant of boron, phosphorous, or arsenic (page 5, claim 26). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Lin to have the resistor made of silicon and a dopant of boron, phosphorous, or arsenic as in Leidy in order to be able to predetermine the device resistivity (Leidy, page 3, paragraph 37).

Claims 45, 47, 66, 68, 91 and 93 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) as applied to claims 48 and 89 above and U.S. Pat. No. 6,495,442 to Lin et al (Lin) in view of U.S. Pat. No. 6,528,380 to Woolery et al. (Woolery) and U.S. Pat. No. 6,486,530 to Sasagawa et al. (Sasagawa) as applied to claim 64 above in further view of and U.S. Pub. No. 2003/0183332 to Simila.

Re claims 45, 47, 66, 68, 91 and 93: Lin discloses the device of 43 and 65 as above. The modification of Woolery also discloses the resistor comprising silicon with a dopant of arsenic (col 9 lines 51 line 6). Lin as modified fails to disclose the resistor comprising silicon with a dopant of phosphorous or gallium. Simila a resistor comprising silicon and a dopant of phosphorous or gallium (paragraph 70). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify

Art Unit: 2811

Lin to have the resistor made of silicon and a dopant of phosphorous or gallium as in Simila in order to be able to predetermine the device resistivity.

Response to Arguments

Applicant's arguments filed 09/25/2008 have been fully considered but they are not persuasive.

Applicant argues that the examiner's interpretation of Lin's disclosure of "transistors and other devices" in the silicon substrate to include resistors is improper because Lin fails to teach what kind of other devices would be thus cannot include resistors. The examiner disagrees. One of ordinary skill in the art at the time the invention was made would interpret "transistors and other devices" to include resistors, as is supported by many references, including the secondary reference Woolery which discloses a silicon substrate with transistors (440) and resistors (420) see Fig 4E. Further, other references disclosing metallization also disclose transistors and resistors within a substrate, for example U.S. Pat. No. 6,261,944 to Mehta et al. (col 3 lines 45-57) and U.S. Pat. No. 5,328,553 to Poon (col 5 lines 33-38).

Applicants arguments with respect to the Carichner reference are moot in view of new grounds of rejection.

Conclusion

Art Unit: 2811

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Colleen A. Matthews whose telephone number is (571)272-1667. The examiner can normally be reached on Monday - Friday 8AM-4:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Lynne Gurley can be reached on 571-272-1670. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/C. A. M./
Examiner, Art Unit 2811

/Lynne A. Gurley/
Supervisory Patent Examiner, Art
Unit 2811